



**PRODUCT DATA SHEET:**

**ANTI FREEZE XL**

**ANTI FREEZE XL** is a good quality modern antifreeze belonging to a generation silicate-holding, nitrit-, amine- and phosphate free cooling fluid composed of mono ethylene glycol and specially selected additives.

**ANTI FREEZE XL** can be used throughout the year in all cooling systems in petrol- and diesel engines .Thanks to the balanced additive package and the high quality mono-ethylene glycol, this standard quality anti freeze is one of the highest quality anti freezes in the market.

**ANTI FREEZE XL** gives the best protection if it is used in concentrations between 40 and 50% in water.

**ANTI FREEZE XL** offers good protection of all metals in the cooling system and engine and is neutral towards seals and flexible hoses.

**WARNING:**

Keep all anti freezes out of reach of children!

Do not drink anti freeze!

If swallowed, induce vomiting and immediately call for a doctor!

TYPICAL PROPERTIES:		SPECIFICATIONS:
PRODUCT CODE	4395	Exceeds: BS 6580, ASTM D3306, SAE J1034 AFNOR 15-601, CUNA NC 956-16 MB 325.2, GM/Opel, Deutz/MWM BMW, VW TL 774C (G11)
DENSITY @ 15°C	1078 kg/m3	
pH 33% in water	8	
Crystallisation Point 40 % in water	-26°C	
Crystallisation Point 50 % in water	-38°C	