



PRODUCT DATA SHEET:

MARINE MGEO 15W-40

MARINE MGEO 15W-40 is a mineral based marine engine oil providing good performance in high output , high speed, turbo charged engines operating under severe conditions.

MARINE MGEO 15W-40 has been formulated with carefully selected additives in mineral base stocks, to provide excellent detergency, dispersancy and anti wear performance.

MARINE MGEO 15W-40 has excellent thermo-oxidative stability, controlling deposits and viscosity increase. Excellent soot handling controls soot induced oil thickening and effectively prevents wear.

MARINE MGEO 15W-40 reduces piston deposits, protects against “Bore Polishing”, reduces oil consumption and allows extended drain intervals.

MARINE MGEO 15W-40 is recommended for turbo charged and naturally aspirated diesel engines such as used on board ships and can also be used in marine transmissions requiring an oil with Allison C-4 specifications.

TYPICAL PROPERTIES:		SPECIFICATIONS:
PRODUCT CODE	4287	Exceeds: API CG-4/CF MB 228.3 MAN 271 Volvo VDS MTU Type 2 Mack EO-L
SAE	15W-40	
DENSITY @ 15°C	885 kg/m ³	
VISCOSITY @ 100°C	14,5 mm ² /s	
FLASH POINT	220°C	
POUR POINT	-30°C	

